

Grade

- CBF-E80 Eco

Description

Excellent resistance to water, steam, ozone ageing and many chemicals. Not suitable for contact with petroleum liquids.

Physical

PROPERTY	TYPICAL VALUE	TEST METHOD
Elastomer	EPDM/SBR	
Colour	Black	
Quality	Economy Commercial	
Hardness	70 Shore A +/- 5A	ISO 7619-1
Specific Gravity	1.4 g/cm ²	ISO 2781
Tensile	3.5 N/mm ²	ISO 37
Elongation	250%	ISO 37
Compression		ISO 815-1
Tear Strength		ISO 34-1
Abrasion mm ³		ISO 4649
Temperature Range	-30 C / + 80 C	

Roll Tolerances – ISO 3302 SW1

Width: +/-2%
Length: +/-2%

Thickness

0.5– 1mm +/- 0.2mm
1.5mm–3mm +/- 0.3mm
4mm–5mm +/- 0.4mm
6mm +/- 0.5mm
8mm +/- 0.7mm
10mm–15mm +/- 1mm
20mm +/- 1.4mm
25mm +/- 1.75mm

Thicknesses available

1mm to 6mm 1.4Mtr x 10Mtr
8mm to 25mm 1.4Mtr x 5Mtr
32mm, 38mm, 40mm, 52mm 1Mtr x 1Mtr

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and descriptions information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The company holds no legal or contractual responsibility for information supplied.

Convertors and suppliers of die cut gaskets, tape, sheeting, fabrications, machined plastic components, rubber mouldings, extrusions and adhesives.

