

Grade:

- CBF-812

Colour:

White/Black

Density:

100-120kgs/m³

Width:

1000mm – 1400mm

Thickness (mm):

2,3,4,5,6,8,10,12,15,18,20

Roll Length:

From 25 to 130 meters according to the thickness

Physical

PROPERTY	UNIT	VALUE	TEST METHOD
Density	kgs/m ³	100-125	
Tensile Strength	kpa	>150	DIN 53571
Elongation at break	%	>120	DIN 53571
Tear Strength	N/mm	>0.7	DIN 53515
Compression Set	%	<20	DIN 53572
Compression Deflection	kpa	0s 2-12 60s 2-7	ASTM 1667
Shore 00 Hardness		7-30	
Water Absorption	%	-	
Compression Waterseal		>90%	U-TEST
Flammability	mm/min	<100 >6mm	FMVSS302
Temperature Range	deg C	-30 / +60	

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and descriptions information concerning our products are compiled from research and are believed to be reliable but are provided for guidance purposes only. The company holds no legal or contractual responsibility for information supplied.

Convertors and suppliers of die cut gaskets, tape, sheeting, fabrications, machined plastic components, rubber mouldings, extrusions and adhesives.

